

Goodspeed

TENNIS comfort pro

(Formerly known as PORPLASTIC TENNIS comfort pro)

Tennis court flooring system for indoor and outdoor point-elastic according to EN 14904, ITF classified

Application Fields

Tennis halls indoor/outdoor



Very Durable



NO Maintenance !



Equal ball reflection

Performance check



Water impermeable



Best in scratch and abrasion resistance



No maintenance



Available in many colours



Easy to clean



Equal ball reflection



Permanent elasticity








Shock absorption of 17 - 30%



ITF certified



Layer		Consumption	Thickness	Application
LINE PAINT Goodspeed X8085 SR		20 – 30 g/lfm	ca. 0.10 – 0.20 mm	Roller or brush
STRUCTURED TOP FINISH Goodspeed S6095 SR		150 – 200g per layer (in 2 layers)	ca. 0.30 mm	Rubber squeegee
SELF LEVELING LAYER Goodspeed C524		ca. 2.00 kg/m ²	ca. 1.50 mm	Notched squeegee
ELASTIC MAT Goodspeed basic L390 M		4.50 – 7.50 kg/m ²	ca. 6 – 10 mm	Notched squeegee
PRIMER FLOORFINDER EP-P210		ca. 0.40 kg/m ²	ca. 0.20 mm	Roller or rubber squeegee

Remark: for further information please refer to the product data sheets or contact our technical service. All data are approximate values. Therefore, no liability claims can be derived from the system data sheet. As all Goodspeed data sheets are updated on a regular basis it is the users' responsibility to obtain the most recent issue (see www.porplastic.com or contact us directly). Date of issue: June 2025 – all technical information is subject to change without prior notice.

